

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An assembly of prefabricated panels comprising:
a plurality of prefabricated panels each having:

a front panel body having an upper end and a lower ~~end~~; end;

an upper bent section formed toward the upper end of the front panel

body, and extending upwardly therefrom to define a coupling recess extending in a longitudinal direction of the panel ~~body~~; body, the coupling recess having a bottom flange extending rearward from the front panel body and a rear flange extending upward from a rear end of the bottom flange;

an engagement protrusion upwardly protruded from the upper end of the front panel body, the coupling recess being forwardly opened above the engagement protrusion and extending in the longitudinal direction of the panel ~~body~~; body, the engagement protrusion, bottom flange, and rear flange forming a securing receptacle; and

a lower bent section rearwardly bent from the lower end of the front panel body while extending in the longitudinal direction of the front panel body, the lower bent section having a rear flange extending downward with respect to the lower end of the front panel body and a bottom flange extending forward from a lower end of the rear flange, the lower bent section of an upper panel of the plurality of prefabricated panels being insertable in the coupling recess of a lower panel of the plurality of prefabricated panels, the rear and bottom flanges of the lower bent section of the upper panel nesting in the securing receptacle of the lower panel, the bottom flange of the lower bent section of the upper panel being positioned contiguous the bottom flange of the coupling recess of the lower panel, the prefabricated panels being vertically aligned while being coupled to one another in such a manner that the lower bent section of an

~~upper one of the prefabricated panels vertically adjacent to each other is fitted in the coupling recess defined by the upper bent section of a lower one of the adjacent prefabricated panels.~~

2. (Original) The assembly of prefabricated panels according to claim 1, wherein each of the prefabricated panels further has at least one reinforcing section rearwardly protruded from a rear surface of the panel body of the prefabricated panel while extending in the longitudinal direction of the panel body to reinforce the panel body.

3. (Previously Presented) The assembly of prefabricated panels according to claim 1, further comprising:

corner finishing members each adapted to finish facing longitudinal ends of the prefabricated panels arranged adjacent to each other at a corner region of the assembly wherein each of the corner finishing members has a diagonal body portion, a pair of outer extensions extending outwardly from opposite ends of the diagonal body portion in horizontal and vertical directions, respectively, a pair of inner extensions extending inwardly from the opposite ends of the diagonal body portion in vertical and horizontal directions, respectively, and a pair of outer claws protruded outwardly from the inner extensions, respectively, whereby the corner finishing member is coupled with the facing longitudinal ends of the prefabricated panels in such a manner that the facing longitudinal ends of the prefabricated panels are fitted between the outer extensions and the outer claws associated therewith, respectively.

4. (Previously Presented) The assembly of prefabricated panels according to claim 1, further comprising:

panel connecting members each adapted to couple facing longitudinal ends of the prefabricated panels longitudinally aligned while being adjacent to each other to define a junction therebetween wherein each of the panel connecting members has a T-shaped body having a horizontal portion and a vertical portion extending vertically, at one end thereof, from a central position of the horizontal portion, and a pair of coupling claws extending inclinedly outwardly from the other end of the vertical portion in the T-shaped body toward the horizontal

portion of the T-shaped body at opposite sides of the vertical portion, respectively, whereby the panel connecting member is coupled with the facing longitudinal ends of the junction-defining prefabricated panels in such a manner that the facing longitudinal ends of the junction-defining prefabricated panels are fitted between the horizontal portion of the T-shaped body and the coupling claws associated therewith, respectively.

5. (Previously Presented) The assembly of prefabricated panels according to claim 1, further comprising:

longitudinal end finishing members respectively adapted to finish longitudinal ends of the prefabricated panels arranged at an end region of the assembly wherein each of the longitudinal end finishing members has an inverted L-shaped body having a horizontal portion and a vertical portion, and a coupling claw extending inclinedly from a substantially intermediate position of the vertical portion in the inverted L-shaped body toward the horizontal portion of the inverted L-shaped body, whereby the longitudinal end finishing member is coupled to the longitudinal end of the prefabricated panel associated therewith in such a manner that the longitudinal end of the associated prefabricated panel is fitted between the horizontal portion of the inverted L-shaped body and the coupling claw associated therewith.

6. (Previously Presented) The assembly of prefabricated panels according to claim 1, further comprising:

upper end finishing members respectively adapted to finish upper ends of uppermost ones of the prefabricated panels wherein each of the upper end finishing members has an S-shaped body having upper and lower bent portions, and a coupling claw extending inclinedly inwardly from an outer tip of the upper bent portion, whereby the upper end finishing member is coupled with the upper end of the uppermost prefabricated panel associated therewith in such a manner that the coupling claw of the upper end finishing member is engaged with a rear surface of the associated uppermost prefabricated panel at the upper end of the associated uppermost prefabricated panel, and that the lower bent portion is fitted in the coupling recess of the associated uppermost prefabricated panel.

7. (Previously Presented) The assembly of prefabricated panels according to claim 1, further comprising:

lower end finishing members respectively adapted to finish lower ends of lowermost ones of the prefabricated panels wherein each of the lower end finishing members has an inverted S-shaped body having an upper bent portion defining a forwardly-opened coupling recess, and an engagement protrusion upwardly protruded from an upper end of the inverted S-shaped body, whereby the lower end finishing member is coupled with the lower end of the associated lowermost prefabricated panel in such a manner that the lower bent section of the associated lowermost prefabricated panel is fitted in the coupling recess of the lower end finishing member.

8. (Previously Presented) The assembly of prefabricated panels according to claim 1, further comprising:

display panel mounting members each coupled with the coupling recess of a selected one of the prefabricated panels, and adapted to mount a display panel for goods to the selected prefabricated panel, each of the display panel mounting members having a hook adapted to be engaged with the engagement protrusion of the prefabricated panel to be coupled with the display panel mounting member, a fitting portion for fitting an end of the display panel therein, and a support portion for supporting the end of the display panel fitted in the fitting portion.

9. (Withdrawn) An assembly of prefabricated panels for a building construction comprising:

first brackets adapted to be directly mounted to a wall of the building construction, each of the first brackets having a vertically-extending strip structure, the first bracket having a plurality of hooks arranged in pairs such that the hook pairs thereof are vertically uniformly spaced apart from one another, and bolt holes provided at each of upper and lower end portions in the first bracket;

second brackets each adapted to be coupled to an associated one of the first brackets, each of the second brackets having a vertically-extending hollow bar structure, the second bracket having a plurality of engagement holes provided at a rear wall portion of the second bracket while being arranged in pairs such that the hole pairs thereof are vertically uniformly spaced apart from one another, each pair of the engagement holes being adapted to be engaged with an associated pair of the hooks in the associated first bracket, and a plurality of hooks provided at a front wall portion of the second bracket while being vertically uniformly spaced apart from one another; and

prefabricated panels each having a panel body, a bent section extending from an upper end of the panel body while being rearwardly and upwardly bent, a first engagement protrusion upwardly protruded from the upper end of the panel body while defining a coupling recess in cooperation with the bent section, and a second engagement protrusion downwardly protruded from a lower end of the bent section, and adapted to be engaged with an associated one of the hooks in each of the second brackets, thereby allowing the prefabricated panels to be supported by the second brackets, and a lower bent section extending from a rear surface of the panel body near a lower end of the panel body while being rearwardly and downwardly bent, the prefabricated panels being vertically aligned while being coupled to one another in such a manner that the lower bent section of an upper one of the prefabricated panels vertically adjacent to each other is fitted in the coupling recess of a lower one of the adjacent prefabricated panels.

10. (Withdrawn) The assembly of prefabricated panels according to claim 1, further comprising:

first brackets adapted to be directly mounted to a wall of the building construction, each of the first brackets having a vertically-extending strip structure, the first bracket having a plurality of hooks arranged in pairs such that the hook pairs thereof are vertically uniformly spaced apart from one another, and bolt holes provided at each of upper and lower end portions in the first bracket;

second brackets each adapted to be coupled to an associated one of the first brackets, each of the second brackets having a vertically-extending hollow bar structure, the

second bracket having a plurality of engagement holes provided at a rear wall portion of the second bracket while being arranged in pairs such that the hole pairs thereof are vertically uniformly spaced apart from one another, each pair of the engagement holes being adapted to be engaged with an associated pair of the hooks in the associated first bracket, and a plurality of hooks provided at a front wall portion of the second bracket while being vertically uniformly spaced apart from one another, wherein each prefabricated panel includes another engagement protrusion downwardly protruded from a lower end of the upper bent section, and adapted to be engaged with an associated one of the hooks in each of the second brackets, thereby allowing the prefabricated panels to be supported by the second brackets.

11. (New) The assembly of prefabricated panels according to claim 1 wherein the front panel body of at least one of the plurality of prefabricated panels is planar.

12. (New) An assembly of prefabricated panels comprising:
a plurality of prefabricated panels each having:
a front panel body having an upper end and a lower end;
an upper bent section formed toward the upper end of the front panel body, the upper bent section extending rearward with respect to the front panel body and defining a coupling recess having a lower end spaced from, and positioned below, the upper end of the front panel body; and
a lower bent section formed toward the lower end of the front panel body, the lower bent section extending rearward with respect to the front panel body and having a lower end, the lower bent section of an upper panel of the plurality of prefabricated panels being insertable in the coupling recess of a lower panel of the plurality of prefabricated panels, the lower end of the lower bent section of the upper panel contacting the lower end of the coupling recess of the lower panel, the lower end of the coupling recess of the lower panel axially supporting the upper panel.